



No measures are required.
 Useable with measures.
 Reduce exposure duration.

model	daily exposure time [h]	time sequence operating mode (idling/ full load/ nom. speed)	standard	equivalent vibration level handle left a hv,eq [m/s ²]	equivalent vibration level handle right a hv,eq [m/s ²]	daily vibration exposure handle left A(8) [m/s ²]	daily vibration exposure handle right A(8) [m/s ²]
TS 410	1,0	1/7 LL - 6/7 ND	ISO 19432	3,9	3,9	1,4	1,4
TS 420	1,0	1/7 LL - 6/7 ND	ISO 19432	3,9	3,9	1,4	1,4
TS 440 A	1,0	1/7 LL - 6/7 ND	ISO 19432	3,6	3,9	1,3	1,4
TS 480i A	1,0	1/7 LL - 6/7 ND	ISO 19432	2,2	2,2	0,8	0,8
TS 500i A	1,0	1/7 LL - 6/7 ND	ISO 19432	2,4	2,0	0,8	0,7
TS 700	1,0	1/7 LL - 6/7 ND	ISO 19432	6,6	4,5	2,3	1,6
TS 800	1,0	1/7 LL - 6/7 ND	ISO 19432	6,5	3,9	2,3	1,4
TS 460	1,0	1/7 LL - 6/7 ND	ISO 8662	3,4	5,9	1,2	2,1

All data is subject to change and applicable to European versions only.